

ECO™ SERIES

The strength you trust, now with ultra low voc.

- Superior joint strength
- Fast setting
- 30% lower solvent emissions
- Less odorous fumes
- Improved working environment



Breathe easier

www.weldon.com

| | Max Pipe Size 最大管徑 | Set Time 乾燥時間 | Available Color 可供貨顏色 | Performance Specification |
|--|---------------------------------------|-------------------------|---|---|
| | 4" (110 mm) Not for Sch. 80 | Fast | <input type="button" value="CLEAR"/> | PW-G/DWW/SW U.P. CODE ASTM D2564 NSF/ANSI 14 & 61 |
| | 6" (160 mm) 4" (110 mm) Sch. 80 | Fast | <input type="button" value="CLEAR"/> <input type="button" value="GRAY"/> | PW-G/DWW/SW U.P. CODE (GRAY ONLY) PW-G/DWW/SW U.P. CODE ASTM D2564 NSF/ANSI 14 & 61 CSA B137.3 CSA B181.2 |
| | 6" (160 mm) 4" (110 mm) Sch. 80 | Fast | <input type="button" value="BLUE"/> | PW-G/DWW/SW U.P. CODE ASTM D2564 NSF/ANSI 14 & 61 |
| | 12" (315 mm) | Medium | <input type="button" value="CLEAR"/> <input type="button" value="GRAY"/> | PW-G/DWW/SW U.P. CODE (GRAY ONLY) PW-G/DWW/SW U.P. CODE ASTM D2564 NSF/ANSI 14 & 61 CSA B137.3 CSA B181.2 |
| | — | — | <input type="button" value="CLEAR"/> <input type="button" value="PURPLE"/> | U.P. CODE (PURPLE ONLY) ASTM F656 NSF/ANSI 14 & 61 |

Irrigation • Pool & Spa • Industrial • Construction/Conduit

