# **Safety Data Sheet**

Conforms to JIS Z 7253 : 2019

No.D-004e-08

Preparation date: May 14, 2010 Revision date: Dec. 17, 2021

Page : 1/9

## 1. Chemicals and Company Information

Chemical name AV Adhesive 88 (low-viscosity quick-drying up)

**SDS No.** No.D-004

Supplier name Asahi Yukizai Corporation

Address 2-5955, Nakanose-cho Nobeoka-city Miyazaki-pref. Japan 882-8688

Phone number +81-982-35-9380 (CS & Quality Section

EHS & CS/QA Department Valve & Piping Systems Division)

Fax number +81-982-35-9358 (CS & Quality Section

EHS & CS/QA Department Valve & Piping Systems Division)

Emergency phone number +81-982-35-9380

Manufacturer Konishi Co., Ltd.

**Recommended use and restrictions on use**Adhesive for PVC pipes. Use only as specified.

### 2. Hazards Identification

#### GHS classification and label elements of the product

Physical hazards Flammable liquids : Category 2

**Health hazards** Acute toxicity (via mouth) : Category 4

Acute toxicity (dermal) : Category 4 Acute toxicity (inhalation: vapor) : Category 4 Skin corrosion/irritation : Category 2 Serious eye damage/eye irritation : Category 2 Skin sensitization : Category 1 Germ cell mutagenicity : Category 2 Carcinogenic : Category 2 Reproductive toxicity : Category 2

: Category 1 (central nervous system, respiratory system)

Specific target organ toxicity (single exposure)

Specific target organ toxicity (single exposure)

: Category 2 (kidney)

Specific target organ toxicity (single exposure)

: Category 3 (Anesthetic effect)

Specific target organ toxicity (single exposure)

: Category 3 (airway irritability)

Specific target organ toxicity (repeated exposure)

: Category 1 (liver, central nervous system, respiratory system, bone, nervous system)

Items for which the GHS classification result is "Not applicable to classification" or "Cannot classify" are not listed .

GHS label elements Symbol (GHS JP)



#### ASAHI YUKIZAI CORPORATION

## **Safety Data Sheet**

Conforms to JIS Z 7253: 2019

No.D-004e-08

Preparation date: May 14, 2010 Revision date: Dec. 17, 2021

Page : 2/9

#### Signal word (GHS JP)

#### **Hazard statement (GHS JP)**

#### Danger

H225: Highly flammable liquid and vapor

H302+H312+H332: Harmful if swallowed or if in contact with skin

or inhaled.

H315: Causes skin irritation

H317: May cause allergic skin reactions.

H319: Causes serious eye irritation

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H341: Suspected risk of hereditary disease

H351: Suspected of causing cancer

H361: Suspected of causing adverse effects on fertility or the unborn child.

H370: Organ damage (central nervous system, respiratory system)

H371: Risk of organ damage (kidney)

H372: Organ damage due to long-term or repeated exposure

(liver, central nervous system, respiratory system, bones, nervous system)

#### Precautionary statement (GHS JP) Safety measures

P201: Obtain the instruction manual before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat / sparks / open flames / hot surface.

- No smoking.

P233: Keep the container tightly closed.

P240: The container shall be grounded and earthed.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use tools that do not generate sparks.

P243: Take measures against electrostatic discharge.

P260: Do not inhale mists/vapors/sprays.

P261: Avoid inhalation of mist/vapor/spray.

P264: Wash hands, forearms and face thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be removed from the workplace.

P280: Wear protective gloves.

First-aid measures

P301+P312: If swallowed: Contact a physician if you feel unwell.

P302+P352: If on skin, wash with plenty of soap and water.

P303+P361+P353: If on skin (or hair), take off immediately all

contaminated clothing. Rinse skin with water/shower.

P304+P340: If inhaled, remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: If in eyes, rinse cautiously with water for several

Remove contact lenses, if present and easy to do.

Continue rinsing.

P308+P311: If there is exposure or concern of exposure, contact a physician.

P308+P313: If there is exposure or concern of exposure, get medical advice/attention.

P312: Call a doctor if you feel unwell.

P314: Get medical advice/attention if you feel unwell.

P321: Specific treatment is required.

P330: Rinse mouth.

P332+P313: If skin irritation occurs, get medical advice/attention.

P333+P313: If skin irritation or rash occurs, get medical advice/attention.

P337+P313: If eye irritation persists, get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

#### ASAHI YUKIZAI CORPORATION

# **Safety Data Sheet**

Conforms to JIS Z 7253 : 2019

No.D-004e-08

Preparation date: May 14, 2010 Revision date: Dec. 17, 2021

Page : 3/9

P370+P378: In case of fire, use appropriate media other than water for

extinction.

Storage P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

**Disposal** P501: Dispose of contents/container in accordance with local/national

regulation.

**Summary of significant candidates** 

and possible emergencies

The product may cause organic solvent poisoning.

## 3. Composition / Information on Ingredients

Single or Mixture Mixture

**Product name**Vinyl chloride resin adhesive

	Concentration	Chemical formula	Reference Number in Gazetted List in Japan		
Component	or concentration range		CSCL (Chemical Substances Control Law)	Labor Safety and Health Act	CAS No.
Cyclohexanone	40-50%	$C_6H_{10}O$	(3)-2376	-	108-94-1
Tetrahydrofuran	30-40%	C <sub>4</sub> H <sub>8</sub> O	(5)-53	-	109-99-9
Methyl ethyl ketone	10-20%	CH <sub>3</sub> CH <sub>2</sub> COCH <sub>3</sub>	(2)-542	-	78-93-3

### 4. First-aid Measures

**Description of first-aid measures** 

**If inhaled** Remove person to fresh air and keep comfortable for breathing.

Get a doctor/physician if you feel unwell.

If on skin Call a doctor immediately.

Wash gently with plenty of soap and water. Remove all contaminated clothing immediately.

Wash skin with running water/shower.

If in eyes Rinse cautious with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Call a doctor immediately.

**If swallowed** Rinse mouth.

Contact a physician immediately.

Do not induce vomiting.

**Protection of first-aiders** Wear appropriate protective equipment.

### 5. Fire-fighting Measures

**Extinguishing media** 

Suitable extinguishing media Powdered chemical fire extinguisher, carbon dioxide or ordinary foam fire

extinguisher, sand/soil.

Un suitable extinguishing media Do not use direct water jet.

Fire Hazards Extremely flammable liquid and vapor.

**Extinguishing Measures** In the event of fire, stop the leak if it can be safely handled.

Conduct fire fighting from a safe distance and protected location.

## **Safety Data Sheet**

Conforms to JIS Z 7253 : 2019

No.D-004e-08

Preparation date: May 14, 2010 Revision date: Dec. 17, 2021

Page : 4/9

## 6. Accidental release Measures

**Protective equipment for fire-fighters** 

Personal precautions, protective equipment and emergency procedures

Non-emergency responder

**Protective equipment** Wear appropriate protective equipment when working.

**First aid measures** Avoid contact with skin and eyes.

Ventilate spilled area.

Do not touch or walk on spilled product. Prohibit entry of non-related personnel.

**Environmental precautions** 

**Environmental precautions** Prevent entry into sewers and public waterways.

Prevent entry into drains or waterways.

Do not release the product into the environment.

Compressed air and oxygen breathing apparatus Wear fire/flame resistant/retardant clothing.

Containment and cleanup methods and equipment

Containment methods In the event of a large spill, contain the spill in a trench and block it with

moist sand or earth for safe disposal afterwards. Contain the leak without risk if possible.

Purification methods If a small amount of liquid is spilled, absorb it with a nonflammable

absorbent and place it in a container for disposal. Absorb all diffused product with sand or soil. Ground all equipment used when handling spills.

## 7. Precautions for Handling and Storage

Handling

**Engineering measures**Use local exhaust ventilation and general ventilation as described in

"8. Exposure controls / Protective measures".

Take equipment measures as described in "8. Exposure controls

/ Protective measures" and wear protective equipment.

**Precautions for safe handling**Do not get on eyes, skin, or clothing.

Do not inhale dust/smoke/gas/mist/vapor/spray. Ensure adequate ventilation of work area.

Keep away from ignition sources such as heat/sparks/open flames/high

temperature items.

No smoking.

No fire and pay attention to static electricity. Refer to "10. Stability and Reactivity."

Sanitary measures Always wash your hands after handling.

Storage

Safe storage conditions Store in a well-ventilated area.

Keep container tightly closed.

Keep out of sunlight.

Storage temperature 2-40 °C

## 8. Exposure controls / Protective measures

Cyclohexanone (108-94-1)		
Control concentration (MHLW)	20ppm	
Allowable concentration	25ppm (100mg/m <sup>3</sup> )	
(Japan Society for Occupational Health)	25ppm (100mg/m )	

Allowable concentration

(Japan Society for Occupational Health)

**ACGIH** 

**ACGIH** 

#### ASAHI YUKIZAI CORPORATION

TWA 20ppm,

TWA 50ppm,

STEL 50ppm (Skin)

STEL 100ppm (Skin)

# **Safety Data Sheet**

Conforms to JIS Z 7253 : 2019

No.D-004e-08

Preparation date: May 14, 2010 Revision date: Dec. 17, 2021

Page : 5/9

Tetrahydrofuran (109-99-9)	
Control concentration (MHLW)	50ppm

Methyl ethyl ketone (78-93-3)		
Control concentration (MHLW)	200ppm	
Allowable concentration	200ppm (590mg/m <sup>3</sup> )	
(Japan Society for Occupational Health)		
ACGIH	TWA 200ppm STEL 300ppm	

**Equipment measures** Provide adequate ventilation.

Install a local exhaust system.

 $50ppm (148mg/m^3)(skin)$ 

Personal protective equipment Wear the recommended personal protective equipment.

Hand protection Wear appropriate protective gloves.

Eye protection Wear appropriate safety glasses.

**Protective equipment for skin and body**Wear long-sleeved work clothes, and protective clothing / protective boots as

necessary.

**Respiratory protection** [If ventilation is inadequate ] Wear protective equipment for breathing.

## 9. Physical and Chemical Properties

Physical state Liquid
Appearance Liquid

**Color** Colorless and semitransparent

**Odor** Petroleum odor

pH No dataBoiling point No data

Flash point -14°C (minimum ignition point used)

Spontaneous combustion pointNo dataDecomposition temperatureNo dataFlammabilityNo dataExplosion limits (vol%)No dataSteam pressureNo data

**Relative Vapor density (20°C)** 1 or more (air =1)

**Density**  $0.97 \text{g/cm}^3$ 

**Temperature of density measurement** 20°C

Relative gas density No data

# **Safety Data Sheet**

Conforms to JIS Z 7253 : 2019

No data

No.D-004e-08

Preparation date: May 14, 2010 Revision date: Dec. 17, 2021

Page : 6/9

**Solubility** Insoluble in water, soluble in organic solvent

Kinematic viscosity 200 ~ 700 mPa·s

Dynamic viscosity measurement temperature 20°C

Dynamic viscosity rate No data

Particle diameter distribution No data

Particle shape No data

Particle aspect ratio No data

Particle specific surface area No data

10. Stability and Reactivity

Particle size

**Reactivity** Under normal conditions of use, storage and transportation, this product will

not react.

Chemical stability Stable under normal conditions.

**Possibility of hazardous reactions**Stable under normal conditions of use.

Conditions to avoid Not applicable.

**Incompatible materials** Avoid contact with oxidizer.

**Hazardous decomposition products**Carbon monoxide (CO).

11. Toxicological Information

Acute toxicity (oral) Harmful if swallowed

**Acute toxicity (dermal)** Harmful when in contact with skin

Acute toxicity (inhalation) Cannot classify (gas)

Harmful if inhaled

Cannot classify (dust, mist)

ATE JP (oral)	1204.405 mg/kg bodyweight
ATE JP (dermal)	1203.999 mg/kg bodyweight
ATE JP (steam)	11.831 mg/l/4h

Skin corrosion / irritation Skin corrosion

Serious eye damage / eye irritation Strong eye irritation

**Respiratory sensitization** Cannot classify

**Skin sensitization** May cause an allergic skin reaction.

Germ cell mutagenicity

Suspected hereditary disease
Carcinogenicity

Suspected of causing cancer

**Reproductive toxicity** Suspected of causing adverse effects on fertility or the unborn child

**Specific target organ toxicity (single exposure)** Organ damage (central nervous system, respiratory system)

Risk of organ damage (kidney) May cause drowsiness or dizziness. Risk of irritation to the respiratory tract

Specific target organ toxicity (repeated exposure) Organ damage due to long-term or repeated exposure (liver, central nervous

system, respiratory system, bones, nervous system)

#### ASAHI YUKIZAI CORPORATION

## **Safety Data Sheet**

Conforms to JIS Z 7253 : 2019

No.D-004e-08

Preparation date: May 14, 2010 Revision date: Dec. 17, 2021

Page : 7/9

Aspiration hazard

Not applicable to classification

### 12. Environmental Impact Information

**Ecosystems - General** When leaking or disposing of the product, be careful not to handle it as it

may affect the environment.

Hazardous to the aquatic environment Short-term hazard (Acute)

Cannot classify

Hazardous to the aquatic environment Long-term hazard (Chronic) Cannot classify

AV Adhesive 88	
Residual and degradability	No data
Bioaccumulative	No data
Mobility in the soil	No data

Hazardous to the ozone layer

Cannot classify

### 13. Disposal Considerations

Contaminated container and package

Paper containers and packaging such as outer boxes and paper tubes:

Collected or disposed of as paper waste (If it is a single substance, it is treated as stable industrial waste. If there is an adhering component, it is also treated as controlled industrial waste too.)

When disposing of empty containers, remove the contents completely and dispose of them as industrial waste or send them for collection.

Metal can, metal drum, and metal tubes: Dispose of as scrap metal. (In the case of a single component, treat as stable industrial waste. If there are adhering components, follow the classification of stable/managed industrial wastes.)

Glass containers: Disposed of as glass waste. (In the case of a single component, treat as stable industrial waste. If there are adhering components, follow the classification of stable/managed industrial wastes.)

Plastic bottles, tubes, bags, etc.: Dispose as waste plastics. (In the case of a single component, treat as stable industrial waste. (If there are adhering components, follow the classification of stable/managed industrial wastes.)

Dispose in accordance with applicable laws and regulations and municipal standards.

Entrust disposal to an industrial waste disposer licensed by the prefectural governor, or to a local public body, if such a body is in charge of disposal.

When disposing of waste, follow the Law Concerning Waste Disposal and Public Cleansing in particular.

When disposing of the product, confirm the reactivity of the hazardous information before processing.

Waste from residues

## No.D-004e-08

Preparation date: May 14, 2010 Revision date: Dec. 17, 2021

Page : 8/9

## Safety Data Sheet

Conforms to JIS Z 7253 : 2019

### 14. Transport Information

International regulations

Road transport (UN RTDG)	Marine transport (IMDG)	Air transport (IATA)		
UN No.				
1133	1133	1133		
UN official product name				
Adhesives	ADHESIVES	Adhesives		
Classification of dangerous	goods for transportation			
3	3	3		
3				
Packing group				
II	II	II		
Environmental Hazardous				
Environmental Hazardous	Environmental Hazardous	<b>Environmental Hazardous</b>		
Not applicable	Not applicable	Not applicable		
	Marine Pollutants			
	Not applicable			

Marine Pollutants Not applicable

**Special transport precautions** Follow the instructions in "7. Precautions for handling and storage"

Check that the containers are free from leakage and load them so as to prevent them from toppling over, falling, and suffering damage and ensure

the prevention of cargo collapse.

**Domestic Regulations** 

Land Regulations When the Fire Service Law, Industrial Safety and Health Law, or Poisonous

and Deleterious Substances Control Law is applicable, the product shall be transported in accordance with the applicable laws and regulations.

**Maritime Regulation** Follow the provisions of the Ship Safety Law.

**Aviation Regulations** Follow the provisions of the Civil Aeronautics Act.

**Emergency Response Guideline Number** 128

Other Information No supplementary information

## 15. Regulatory Information (in Japan)

Industrial Safety and Health Low Second class organic solvent, etc. (Enforcement Ordinance, Schedule 6-2;

Ordinance on the Prevention of Organic Solvent Poisoning, Article 1,

Paragraph 1, Item 4)

Working Environment Assessment Standard

(Article 65-2, Paragraph 1 of the Law)

Hazardous and toxic substances whose names must be indicated

#### ASAHI YUKIZAI CORPORATION

## **Safety Data Sheet**

Conforms to JIS Z 7253 : 2019

No.D-004e-08

Preparation date: May 14, 2010 Revision date: Dec. 17, 2021

Page : 9/9

(Article 57-1 of the Act, Article 18, Item 1 and Item 2 of the Enforcement Order, Appended Table 9)

Hazardous / flammable material

(Enforcement Ordinance, Schedule 1, Item 4)

Hazardous and toxic substances whose names must be notified

(Article 57-2 of the Act, Article 18-2, Item 1 and Item 2 of the Enforcement

Order, Appended Table 9)

Cyclohexanone (Government Ordinance No.231) (40 ~ 50%)
Tetrahydrofuran (Government Ordinance No.367) (30 ~ 40%)
Methyl ethyl ketone (Government Ordinance No.570) (10 ~ 20%)

Poisonous and Deleterious Substances Control Law Not applicable

Fire Service Act Category 4, Class 1 petroleum (water-insoluble) No fire Hazard class II

Foreign Exchange and Foreign Trade Act Export Trade Control Order, Appended Table 1-16

Ship Safety Act Flammable liquids (Regulations for the Carriage and Storage of Dangerous

Goods in Ships, Articles 2 and 3; Hazardous Materials Notification,

Schedule 1)

Civil Aeronautics Act Flammable liquids (Civil Aeronautics Law Enforcement Regulations, Article

194; Hazardous Materials Notification - Schedule 1)

**Act on Port Regulations**Other hazardous materials / flammable liquids (Article 21-2 of the Law;

Article 12 of the Regulations; Notification specifying the types of dangerous

goods, separate table)

Pollutant Release and Transfer Register Not applicable

### 16. Other Information

The evaluation of hazards and hazardous properties is not always satisfactory, so please handle with care.

If you have a Safety Data Sheet for this product that was previously given to you, please destroy it.

The SDS is subject to revision due to changes in laws and regulations, product improvements, etc.

If the date of creation or revision is more than two years ago, please confirm that it is the latest version.

SDS transmission route: In principle, Safety Data Sheets (SDS) are transmitted to end users through the following route.

If you have not obtained the SDS yet, please contact us through the sales channel to request the SDS or to inquire about the latest version.

(Manufacturer agency handling business)

#### Disclaimer

The information contained in this sheet is based on reliable information, but no warranty, express or implied, is given as to the accuracy of the information. Because the conditions under which the product is handled, used, stored, or disposed of are beyond our control and may not be known to us, we assume no responsibility, direct or indirect, for any loss, damage, or expense resulting from the handling, use, storage, or disposal of the product. This sheet should be used only with this product. If this product is used as an ingredient in other products, the information contained in this sheet may not apply.